


# 2015 TYRE PATTERN GUIDE

## AGRICULTURE



ZHONGCE RUBBER GROUP CO., LTD.

[www.zc-rubber.com](http://www.zc-rubber.com)







- A Company established in Year 1958
- No. 1 Tyre Manufacturer in China
- No. 10 of Top 75 Global Tyre Manufacturers in Year 2014
- Sale revenue reached \$4.53 billion in Year 2014

Zhongce Rubber Group Co., Ltd. (ZC-RUBBER) takes great pride in producing tyres that rate among the best in the world. Our corporate philosophy is all about collaboration with our suppliers, with over 10,000s of companies who sell our products around the world, and with our millions of end customers who trust our tyres every single day.

Our engineers are working together closely with our international Research and Development (R&D) team combined of Japanese and Korean experts. We keep on investing millions of US dollars in establishing various production and testing facilities such as the first noise test laboratory in China and the MTS Flat-Trac III CT tyre Test

System. Since 2012, we joined and maintained the rank of the global top 10 tyre manufacturer.

Our belief in producing quality tyres makes us to set up quality control system approved by both global tyre manufacturers and the famous car makers such as VOLVO, introduce world latest production facilities from Fischer, VMI, Krupp, etc, and inspect every single tyre by hand before it leaves the production line besides the X-ray, balancing and uniformity inspection by most advanced equipments imported from Germany, Japan and U.S.A. We guarantee our tyre quality by system, facilities and employees' responsibility.

<b>Manufacturing Bases</b>				
<b>Advanced Production Facility</b>				
<b>Strict Quality Inspection</b>				
<b>R&amp;D Center</b>				





# Agriculture Tyre



## Agriculture



### CB538

Size	TRA Code	Ply Rating	LUG #	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure	
								(KG)	(KPA)
8.3-24	R-1	C/6	18	30.0	W7	995	210	810	240
8.3-24	R-1	D/8	18	30.0	W7	995	210	950	300
9.5-24	R-1	D/8	19	33.0	W8	1050	240	1110	280
11.2-24	R-1	B/4	17	35.0	W10	1105	285	750	120
11.2-24	R-1	C/6	17	35.0	W10	1105	285	950	180
11.2-24	R-1	D/8	17	35.0	W10	1105	285	1150	240
12.4-24	R-1	B/4	17	36.0	W11	1160	315	850	110
12.4-24	R-1	C/6	17	36.0	W11	1160	315	1090	170
12.4-24	R-1	D/8	17	36.0	W11	1160	315	1285	220
14.9-24	R-1	B/4	17	38.0	W13	1265	378	1090	100
14.9-24	R-1	C/6	17	38.0	W13	1265	378	1360	140
14.9-24	R-1	D/8	17	38.0	W13	1265	378	1600	180
11.2-28	R-1	B/4	18	35.0	W10	1205	285	800	120
12.4-28	R-1	B/4	19	36.0	W11	1260	315	900	110
12.4-28	R-1	C/6	19	36.0	W11	1260	315	1150	170
12.4-28	R-1	D/8	19	36.0	W11	1260	315	1510	230
13.6-28	R-1	C/6	19	36.0	W12	1310	345	1285	150
14.9-28	R-1	C/6	18	38.0	W13	1355	360	1450	140
14.9-28	R-1	D/8	18	38.0	W13	1355	360	1700	180
14.9-28	R-1	E/10	18	38.0	W13	1355	360	2120	230
16.9-28	R-1	C/6	19	39.0	W15L	1430	408	1650	120
16.9-28	R-1	D/8	19	39.0	W15L	1430	408	1950	170
14.9-30	R-1	D/8	21	39.0	W13	1407	360	1750	180
14.9-30	R-1	E/10	21	39.0	W13	1407	360	1950	220
16.9-30	R-1	C/6	20	39.0	W15L	1464	416	1700	120
16.9-30	R-1	D/8	20	39.0	W15L	1464	416	2000	170
16.9-30	R-1	F/12	20	39.0	W15L	1464	416	2500	230
18.4-30	R-1	C/6		38.0	DW16A	1552	467	1900	110
18.4-30	R-1	D/8		38.0	DW16A	1552	467	2815	140
18.4-30	R-1	F/12		38.0	DW16A	1552	467	3180	230
11-32	R-1	C/6	20	36.0	W10	1450	296	1080	160
16.9-34	R-1	D/8	23	39.0	W15L	1582.5	404	2120	170
16.9-34	R-1	E/10	23	39.0	W15L	1582.5	404	2360	190
18.4-34	R-1	C/6		40.0	W16L	1654	467	2000	110
18.4-34	R-1	F/12		40.0	W16L	1654	467	3375	230
11.2-38	R-1	B/4	22	30.0	W10	1443	270	950	120
12-38	R-1	D/8	22	36.0	W11	1514	315	1600	220
12.4-38	R-1	B/4	22	36.0	W11	1514	315	1060	110
12.4-38	R-1	D/8	22	36.0	W11	1514	315	1600	220
13.6-38	R-1	C/6	23	36.0	W12	1555	325	1500	150
14.9-38	R-1	C/6	23	38.0	W13	1605	356	1870	140
14.9-38	R-1	D/8	23	38.0	W13	1605	356	2180	180
15.5-38	R-1	C/6	22	37.5	W14L	1552	382	1600	140
15.5-38	R-1	D/8	22	37.5	W14L	1552	382	1850	180
16.9-38	R-1	C/6	28	39.0	W15L	1685	404	1900	120
16.9-38	R-1	D/8	28	39.0	W15L	1685	404	2240	170
18.4-38	R-1	C/6		40.0	W16	1755	467	2380	110
18.4-38	R-1	D/8		40.0	W16	1755	467	2715	140
20.8-38	R-1	D/8		40.0	W18L	1835	528	3090	130
20.8-38	R-1	F/12		40.0	W18L	1835	528	4000	200
24.5-32	R-1	F/12		43.0	DW21A	1805	620	4000	170
24.5-32	R-1	G/14		43.0	DW21A	1805	620	4375	190
30.5L-32	R-1	F/12		43.0	DW27A	1845	775	4250	140
30.5L-32	R-1	H/16		43.0	DW27A	1845	775	5000	180
230/95-48	R-1	H/16		32.0	W7	1656	229	2000	320



# Agriculture



## CB558

Size	TRA Code	Ply Rating	LUG #	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure	
								(KG)	(KPA)
7.50-20	R-1	D/8	18	26.0	5.50F	910	205	900	280
9.5-20	R-1	D/8	16	31.0	W8	950	240	955	280
8.3-24	R-1	C/6	17	30.0	W7	995	210	810	240
9.5-24	R-1	D/8	18	31.0	W8	1050	240	1110	280
11.2-24	R-1	D/8	16	33.0	W10	1105	285	1225	240
12.4-24	R-1	D/8	17	36.0	W11	1160	315	1415	230
14.9-24	R-1	D/8	18	38.0	W13	1265	378	1760	180
12.4-28	R-1	C/6	20	32.0	W11	1260	315	1275	170
12.4-28	R-1	D/8	20	32.0	W11	1260	315	1510	230
12.4-28	R-1	F/12	20	32.0	W11	1260	315	1930	350
13.6-28	R-1	F/12	20	43.0	W12	1310	345	2085	290
14.9-28	R-1	D/8	20	38.0	W13	1365	378	1880	180
16.9-30	R-1	D/8	20	41.0	W15L	1464	405	2245	170
18.4-30	R-1	D/8	20	43.0	W16L	1544	444	2415	140
18.4-30	R-1	E/10	20	43.0	W16L	1544	444	2815	180
16.9-34	R-1	D/8	23	41.0	W15L	1580	405	2380	170
16.9-34	R-1	E/10	23	41.0	W15L	1580	405	2605	220
18.4-34	R-1	D/8	21	43.0	W16L	1647	444	2300	140
18.4-34	R-1	E/10	21	43.0	W16L	1647	444	2990	180
18.4-38	R-1	E/10	23	43.0	W16L	1748	444	3165	180



## CR520

Size	TRA Code	Ply Rating	LUG #	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure	
								(KG)	(KPA)
4.00-16	F2	B/4		12.0	3.00D	640	120	300	340
5.50-16	F2	C/6		14.5	4.00E	710	150	525	370
6.00-16	F2	C/6		14.0	4.00E	740	160	560	340
6.00-16	F2	D/8		14.0	4.00E	740	160	675	450
7.50-16	F2	C/6		20.0	5.50F	810	205	745	280
7.50-16	F2	D/8		20.0	5.50F	810	205	870	370

# Agriculture



## CB530

Size	TRA Code	Ply Rating	LUG #	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure	
								(KG)	(KPA)
6.00-12	R-1	C/6	14	24.0	4.50E	640	165	405	250
6.00-12	R-1	C/6	17	24.0	4.50E	640	165	405	250



## CB540

Size	TRA Code	Ply Rating	LUG #	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure	
								(KG)	(KPA)
8.3-20	PR-1	C/6	14	70.0	W7	950	210	970	270
8.3-20	PR-1	D/8	14	70.0	W7	950	210	1130	350
8.3-24	PR-1	C/6	15	70.0	W7	1050	210	1135	270
8.3-24	PR-1	D/8	15	70.0	W7	1050	210	1275	330
9.5-24	PR-1	C/6	15	80.0	W8	1150	240	1315	240
9.5-24	PR-1	D/8	15	80.0	W8	1150	240	1475	290
11.2-24	PR-1	C/6	16	82.0	W10	1205	285	1465	210
12.4-28	PR-1	D/8	18	85.0	W11	1315	315	1785	200





# Forest Tyre

## Forest



### CL710

Size	Ply Rating	Service Index	Standard Rim	Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity (KG)	Cold Inflation Pressure (KPA)
11.00-20	18		8.00	35.0	1105	293	3135	650
11.00-20	20		8.00		1105	293	3410	750
12.00-20	18		8.50		1145	315	3585	650
12.00-20	20		8.50		1145	315	3900	750
12.00-24	20		8.50		1275	315	3750	550



### CL711

Size	Ply Rating	Service Index	Standard Rim	Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity (KG)	Cold Inflation Pressure (KPA)
12.00-24	20		8.50	35.0	1275	315	3750	550



# Forest



## CL969

Size	Ply Rating	Service Index	Standard Rim	Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity (KG)	Cold Inflation Pressure (KPA)
12.00-24	J/18		8.50	23.0	1225	315	4195	810
12.00-24	L/20		8.50	23.0	1225	315	4500	880

